



CEILING TYPES

- △ ACUSTICAL TILE 2'x4'
- △ ACUSTICAL TILE 2'x4' - 1 HOUR FIRE-RATED
- △ 5/8" GYPSUM BOARD
- △ 5/8" GYPSUM BOARD - 1 HOUR FIRE-RATED
- △ 3/8" METAL FACED EXTERIOR PLYWOOD
- △ METAL CEILING
- △ PRECAST CONCRETE
- △ METAL TILE 2'x2'

SYMBOLS

- FULL HEIGHT PARTITION - SEE DETAILS A/5,1 AND A/9,1 FOR TYP. CONNECTION AT ROOF
- FULL HEIGHT PARTITION (1 HR. FIRE RATED CORRIDOR SMOKE WALL) - SEE DETAIL A/5,1
- PARTITION HEIGHT TO APPROX. 4" ABOVE CEILING, STOP MASONRY AT FIRST COURSE ABOVE CEILING - BRACE ALL WALLS OVER 10 FEET LONG - SEE DETAIL B/5,1
- SPRINKLER HEAD IN CEILING

CEILING NOTES

1. (+9'-4") DENOTES HEIGHT OF BOTTOM OF CEILING ABOVE FINISH FLOOR (+0'-0").
2. CONTROL JOINTS (C.J.) FOR GYPSUM WALLBOARD SHALL BE DETAIL A/9,5.
3. WALL ANGLE FOR ACUSTICAL CEILING SHALL BE NARROW STYLE WITH 9/16" FACE.
4. PROJECTION SCREENS AND WINDOW BLINDS ARE BY OWNER. SEE SCREEN DETAIL B/9,5 FOR SUPPORT-BLINDS ARE BY OWNER.
5. RETURN GYPSUM WALLBOARD VERTICALLY WHERE CEILING HEIGHTS OFFSET.

**ADVANCED
TECHNOLOGY
CENTER -
DMACC**

ANKENY, IOWA

REFLECTED CEILING PLAN

1/8"=1'-0"

